

Manage all stations in the network via RCCMD



- Shutdown
- Messaging

Network Connectivity

- Web Based Configuration Interface
- 10Mbit-100Mbit-1Gbit Networks
- Remote Scripting
- RCCMD Network Messaging
- SNMP V2, V3
- SNMP RFC1628 Network Interface
- Email / EmailTrap
- MODBUS over IP
- BACnet over IP
- Build in SFTP Functions
- Event-, Data and Environmental Log
- RSyslog
- RADIUS
- Network Diagnostic Tools

CS141LM-6


External Version



Compatible with different UPS Products, STS/ATS and Power Generators

Options for CS141LM-6

- SENSORMANAGER „SENSMC121“ *
 - Temperature Sensor „SM_T_COM“ *
 - Temperature and Humidity Combi Sensor „SM_T_H_COM“ *
- * = Required: „KABSMTDB9“ cable



CS141SCM-6

Slot Version



Option MODBUS for Facility Management

- MODBUS RS485
 - Indicating Instruments
 - UPS
- = Compatible with different UPS Products and Power Generators



Setup for dry contact and add-ons

- AS400 Adapter „AS400AUX4“
- Alarm Buzzer „CS141_BUZ“
- Relay Board „CON_R_AUX4“
- Connection Terminal „CON_AUX4“

BACS - Battery Management System



- BACS BUS Interface „GX_R_AUX“